CounterAttack LED

120V Switchable Color Temperature

Linkable Series

Catalog #: Type:
Project: Date:
Notes:

4-3/4"

- 8", 16", 24" or 32" →

Order Matrix

CounterAttack Order Matrix (Example: NCA-LED-32-BZ-1)

Se	eries	Length	Finish	Rev
N	CA-LED	-8 (8") -16 (16") -24 (24") -32 (32")	-WT (White) -BZ (Bronze -SM (Silver Metallic)	-1





Interlink Cables

Cable Length	Finish	Rev
NCA-LED-CRD-10 (10") NCA-LED-CRD-18 (18")		-1

Cord and Plug

Cable Length	Finish		Rev
NCA-LED-PLG	WT BK	(White) (Black)	-1



Master Switch (3" x 5" x 1-3/8")

musici diritori (d. x d. x i d/d.)			
Switch	Finish		Rev
NCA-LED-MS	WT BZ SM	(White) (Bronze) (Silver Metalic)	-1

Electrical Data

Part Number	Wattage	Lumens	Efficacy
NCA-LED-8 (8")	5W	300lm	60lpw
NCA-LED-16 (16")	10W	600lm	60lpw
NCA-LED-24 (24")	15W	900lm	60lpw
NCA-LED-32 (32")	20W	1200lm	60lpw

Specifications

Description

Low profile CounterAttack series with integral electronic driver provides even illumination on all surfaces. Available in four lengths and three finishes.

LED Light Engine

- 5W, 10W, 15W or 20W LED
- 2700K or 3000K at 90 CRI (can be switched in the field with an integral rocker)
- 50,000 hours at 70% lumen maintenance (L70)

Electrical

- · Integrated 120V driver
- Incandescent and ELV dimmable
- · Linkable up to 600W

Mounting

Includes mounting hardware (captive screws). Can be hardwired at any point along the run or plugged into receptacle with a cord and plug (ordered separately).

Housing

- Slim 1-3/8" profile
- · Formed steel housing
- · Acrylic lens eliminates LED image

Finishes

Available in white, bronze or silver metallic

Linkable Cables and Connectors

CounterAttack can link multiple luminaires up to 600W with male and female connectors on the ends. Linkable with 10" or 18" interlink cables or end-to-end with seamless connectors.

On/Off Switch

CounterAttack series can be controlled from individual on/off switches or from one master switch. Master switch can be directly connected to the end of a run or moved to a discrete area with interlink cables. (order separately)

Listing/Warranty

- Five (5) year limited warranty
- UL listed to US and Canadian standards for damp locations
- · Title 24 compliant



