



Circulator
 - Cast iron
 - 3-speed, direct drive, wet rotor, inline
Model 2801.9US

Circulator	Wt [lb]	Quantity	Part No	DG
high head	10.247	1	12127	4



Flange set
Components
 (2) flanges, (2) sealing elements, (4) nuts,
 (4) bolts
Model 2881.9US

d	Wt [lb]	Quantity	Part No	DG
¾	2.234	1	16207	4
1	2.329	1	16209	4
1¼	1.915	1	16211	4
1½	1.915	1	16212	4



Spring check valve
 - For prevention of gravity circulation or backflow
 - Female pipe thread
 - Horizontal or vertical installation, non-ferrous
Model 2873.4US

FPT1	FPT2	Wt [lb]	Quantity	Part No	DG
½	½	0.255	1	20201	4
¾	¾	0.400	1	20202	4
1	1	0.562	1	20203	4
1¼	1¼	0.800	1	20204	4
1½	1½	1.100	1	20205	4



Sensor well
 - For housing temperature sensor
 - Suitable for basic heating control
 Model 2871.0US
 - Fits into solder cup or Viega ProPress fitting
Model 2801.4US

CTS	Wt [lb]	Quantity	Part No	DG
½	0.080	1	12128	4



Heat exchanger
 - Brazed stainless steel
Model 2859US

W [in]	L [in]	H [in]	Plates	Wt [lb]	Quantity	Part No	DG
5	12	1.8	16	8.343	1	22006	4
5	12	3.6	36	14.856	1	22007	4
5	12	6.7	70	28.992	1	22008	4



Pressure differential valve
 - Brass
 - Female pipe thread
Model 2871.8US

FPT	Wt [lb]	Quantity	Part No	DG
1	2.069	1	20102	4
1¼	3.159	1	20103	4



Zip tie
 - Plastic
Model 2866US

L [in]	Version	Wt [lb]	Quantity	Part No	DG
8.7	yellow	0.003	100	15304	4